

## Product Information

DE-F900



|                                 |   |
|---------------------------------|---|
| <b>Material description:</b>    | paper, wood-free satin, white, matt surface;<br>good low temperature properties;<br>approved for direct contact with dry and moist, non-greasy food |
| <b>Applications:</b>            | Labeling on all common substrates, also on non-polar surfaces, foils, cardboard and on corrugated cardboard   |
| <b>Label stock thickness:</b>   | 66 µm, 68 g/m <sup>2</sup>  |
| <b>Adhesive:</b>                | AW2: acrylic adhesive, water-based  |
| <b>Adhesive thickness:</b>      | 11 µm ± 10%   |
| <b>Adhesion:</b>                | permanent adhesive  |
| <b>Adhesion power:</b>          | initial tack: glass 15 N FTM 9<br>Peel adhesion 90°: St. St. 2 N/25 mm FTM 2  |
| <b>Liner:</b>                   | brown, glassine paper   |
| <b>Liner thickness:</b>         | 49 µm, 55 g/m <sup>2</sup>  |
| <b>Total thickness:</b>         | 126 µm ± 10%  |
| <b>Temperature range:</b>       | - 20°C to + 80°C  |
| <b>Application temperature:</b> | > + 5°C   |
| <b>Print method:</b>            | thermal transfer printing, flexographic printing, offset printing   |
| <b>Ribbon recommendation:</b>   | DE-R21, DE-R58<br>(each on an unprinted material surface)   |
| <b>Shelf life:</b>              | 2 years at max. 20-25°C and 40-50% rel. humidity<br>without direct sunlight   |

### Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.