

## Product Information

DE-F910



<b>Material description:</b>	pigmented white woodfree paper label with a high degree of brightness; modified acrylic adhesive and super calendered glassine paper, siliconised on one side
<b>Applications:</b>	all-purpose paper label, ideal for EDP applications, with a wide temperature range; high adhesion, especially to cold and moist polyethylene surfaces, approved for indirect food contacts, corresponding to UNI-EN 71/3 "toys security" norms
<b>Label stock thickness:</b>	74 µm, 75 g/m <sup>2</sup>
<b>Adhesive:</b>	modified acrylic adhesive in water emulsion
<b>Liner:</b>	super calendered glassine paper, siliconised on one side; colour: honey
<b>Liner thickness:</b>	54 µm, 60 g/m <sup>2</sup>
<b>Temperature range:</b>	- 20° C to + 80° C
<b>Application temperature:</b>	> +5 ° C
<b>Adhesion:</b>	tack 1600g/25mm cohesion (min) 2hrs
<b>Print method:</b>	thermal transfer

### Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

**Dynamic Systems GmbH** • Inninger Straße 11 • 82237 Wörthsee • phone: 08153/9096-0 • fax: 08153/9096-96  
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.0