

## Product Information

DE-F603



<b>Material description:</b>	Gloss white polyethylene film with a print receptive acrylic top coating. Good conversion and application properties with excellent dispensing ability.		
<b>Applications:</b>	This product is mainly used in the food and toiletries industries and for production of labels for squeezable bottles and cans (e.g. H.D.P.E.) such as for shampoo, toiletries and food packaging.		
<b>Label stock thickness:</b>	100 ±8 µm, 99 ±7 g/m <sup>2</sup>		
<b>Adhesive:</b>	Permanent acrylic, emulsion based adhesive with high adhesion and tack properties on non-polaric and difficult substrates.		
<b>Liner:</b>	Glassine backing paper specially designed for high speed conversion processes. Good translucent properties especially suited to automatic label applicators by optical scanning.		
<b>Liner thickness:</b>	55 ± 4 µm, 65 ± 4 g/m <sup>2</sup>		
<b>Temperature range:</b>	-10° C to + 80° C		
<b>Application temperature:</b>	> +5°C		
<b>Adhesion:</b>	quick tack	≥ 8N/25 mm on glass	FTM9
	Final peel (20 min.)	≥ 7N/25 mm on glass	FTM1
	Cohesion	≥ 30 hours on glass	FTM8
<b>Shelf life:</b>	3 years at 15-25° C and 50 % relative humidity		

### Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.